

Active Temperature Controlled RKN Container



RKN

Scope of Application:

This product is applicable for international aviation cold chain transportation of drugs, vaccines, medicines, biological products, raw materials, premium fresh food and other products which require strict temperature control.

Innovative Design

- Safe, reliable and secure
- Superior temperature uniformity
- Robust construction
- Automatic switching between AC power supply and built-in battery power supply

Qingdao Haier Biomedical Co., Ltd.
Qingdao HB TempCon Aviation Co., Ltd

No.280 Feng Yuan Road, High-tech Zone,
Qingdao, 266109, P.R. China
Tel: +86-400-863-0863
E-mail: aviation@haierbiomedical.com
Website: www.hbtempconaviation.com



HB TempCon
aviation



HB TempCon
aviation



鸿鹄航空科技




@haiermedicalint




Haier Biomedical
International

Qingdao HB TempCon Aviation Co., Ltd. (HB TempCon) is a subsidiary of Qingdao Haier Biomedical and specialized in providing aviation temperature control services. HB TempCon is committed to becoming the aviation temperature control expert and will persist in providing professional solutions for transporting temperature sensitive goods including pharmaceuticals, vaccines, biological products and bulk drugs for the global customers with top quality, high reliability and efficiency.

Product Advantages

 Robust construction with advanced technology to ensure reliable quality and stable performance

 Prevent internal temperature deviation and ensure the temperature uniformity under extreme environmental temperature changes

 Superior internal temperature uniformity

 Cost-effective performance

Specifications

Power

Supports automatic switching between external AC power supply and built-in battery power supply, which is convenient to use and simple to operate

Recharging power supply	100-240V AC, 50-60Hz
Maximum charging time (h)	10 (fast charging)
Maximum power during charging (w)	1, 100

Temperature Control Performance

The ACS/ATC temperature management system, developed independently, achieves accurate temperature control through compressor refrigeration and electric heating innovative air circulation system to effectively balance the temperature difference

Temperature range	Internal temperature tolerance	
0°C~+25°C (+32°F to +77°F)	At set temperature +2°C~+10°C (+35.6°F to +50°F), Tolerance +/-3°C (+/-5.4°F)	
	At set temperature +10°C~+20°C (+50°F to +68°F), Tolerance +/-5°C (+/-9°F)	
Battery capacity	Operating ambient temperature	Storage ambient temperature
When the ambient temperature is 25°C (77°F), the set temperature is 5°C (41°F), the container can operate for more than 50 hrs.	-20°C~+43°C (-4°F to +109.4°F)	-40°C~+55°C (-40°F to +131°F)

Construction

Internal effective volume	Exterior dimensions (L*W*H)	Interior dimensions (L*W*H)	Door opening (L*H)
2m³ (70.6 foot³)	2005*1534*1620mm (78.9*60.4*63.8in)	1294*1273*1264mm (50.9*50.1*49.8in)	1294*1264mm (50.9*49.8in)

Weight

Tare weight	Operational maximum gross weight	Maximum payload
650kg (1433lbs)	1588kg (3500lbs)	938kg (2067lbs)

Data Recording

Data recording function: internal and external temperature, door opening times, alarm information through USB port

Others

Applicable Aircraft Models: A330, A350, A380, B747, B767, B777, B787 as key examples

Note

Tare weight and maximum payload might vary due to load variations and maintenance

*Typical prototype test data

Haier Biomedical reserves the right to change products and specifications without prior notice.